



Ref. **3507**

Matryca ręczna NPT



Standardowy gwint amerykański do uszczelniania rur i kształtek


Faza 1,75 gwintu



NPT	Hilos Threads Filets	D mm	E mm	N° Art. HSS	€
NPT 1/8	27,00	30	11	76043	62,73
NPT 1/4	18,00	38	14	77707	62,73
NPT 3/8	18,00	45	18	22395	81,77
NPT 1/2	14,00	45	18	45894	81,77
NPT 3/4	14,00	55	22	76052	149,54
NPT 1"	11,50	65	25	63476	179,81
NPT 1"1/4	11,50	75	26	22456	223,41
NPT 1"1/2	11,50	90	27	22460	311,70
NPT 2"	11,50	105	28	22475	433,93


Ref. **3502**

Ręczna matryca do BSW



Norma brytyjska dla gwintu grubego

Faza 1,75 gwintu



W	Hilos Threads Filets	D mm	E mm	N° Art. HSS	€
W3/32	48	16	5	63344	37,46
W1/8	40	20	5	63329	30,26
W5/32	32	20	7	63356	31,52
W3/16	24	20	7	63341	31,52
W7/32	24	20	7	63365	41,32
W1/4	20	20	7	63323	30,26
W5/16	18	25	9	63350	31,52
W3/8	16	30	11	63335	45,66
W7/16	14	30	11	63362	45,66
W1/2	12	38	14	63320	45,66
W9/16	12	38	14	63368	54,68
W5/8	11	45	18	63347	66,42
W3/4	10	45	18	63332	66,42
W7/8	9	55	22	63359	97,67
W1"	8	55	22	63374	97,67
W1" 1/8	7	65	25	63383	153,74