

Ref. **3185**

Śruba z gwintem wewnętrznym



HSS

DIN
357Tol.
6H*

*na zamówienie

Stożkowa fazka 18 gwintów

M	P	L mm	I mm	a mm	Z	N° Art. HSS	€
M3	0,50	70	22		3	16332	18,92
M4	0,70	90	25	2,10	3	16333	18,92
M5	0,80	100	28	2,70	3	16334	18,92
M6	1,00	110	32	3,50	3	16335	18,92
M7	1,00	110	36	4,30	3	16336	24,05
M8	1,25	125	40	4,90	3	16337	22,35
M10	1,50	140	45	5,50	3	16338	26,15
M12	1,75	180	50	7,00	3	16339	42,83
M14	2,00	200	56	9,00	3	16340	52,68
M16	2,00	200	63	9,00	3	16342	67,71
M18	2,50	220	63	11,00	3	59877	72,90
M20	2,50	250	70	12,00	3	16343	100,88
M22	2,50	280	80	14,50	3	59878	108,13
M24	3,00	280	80	14,50	3	59879	127,55

Ref. **3099**

Wiertło do kranów

HSSE
5%CoTol.
6HWiertło
do
gwintów

M	P	D Wiercenie mm	L mm	I Wiercenie mm	I Gwint mm	d mm	a mm	N° Art. 5% Co	€
M3	0,50	2,50	56	16,00	11,00	3,00	2,40	63294	28,88
M4	0,70	3,30	63	18,00	14,00	4,00	3,00	63297	28,88
M5	0,80	4,20	71	20,00	18,00	5,00	3,80	63300	32,33
M6	1,00	5,00	80	22,00	22,00	6,00	4,90	63303	43,69
M8	1,25	6,80	95	26,00	25,00	8,00	6,20	63306	55,02
M10	1,50	8,50	106	30,00	31,00	10,00	8,00	63309	74,77
M12	1,75	10,20	115	32,00	35,00	12,00	9,00	63312	79,31

TECHNOGRUPA
Twój wybór